

ACC LeakBlock

WATERPROOF PLASTER - LB 101



ACC LeakBlock Waterproof Plaster - LB 101 is a ready to use cementitious waterproof mortar suitable for Internal & External plaster application. The unique formula consist of ACC cement ,Well graded sand & Special waterproofing & self curing additives.

KEY FEATURES & ADVANTAGES

- Self curing
- Excellent water resistance capability
- Efflorescence resistance
- Higher bond Strength
- Less Rebound Loss
- Saves Time/Cost
- High coverage
- Easy to use and apply, just add water
- Dual function plaster & Patch repair

USES & APPLICATIONS



External plastering of walls



Internal plastering of walls & ceilings



Other general purpose repair & patch work

SURFACE PREPARATION, MIXING & APPLICATION

Step 1



Clean the surface to remove dust and loose particles

धूल और बिखरे कणों को हटाने के लिए सतह को साफ करें

Step 2



Mix with 2.4 - 2.8 litres of water to get the right consistency

सही गाढ़ापन प्राप्त करने के लिए 2.4 - 2.8 लीटर पानी में मिलाएं

Step 3



Apply using trowel to get a coverage of 10 - 12 sq. ft.

10 - 12 वर्ग फुट का कवरेज पाने के लिए ट्रॉवेल से लगाएं

TECHNICAL INFORMATION

- Mixed density :-1.8-1.95 Kg/ltr
- Bulk density :- 1.60-1.8Kg/ltr
- 28 day compressive strength :-10-15Mpa
- Pull-out bond strength :- ≥ 0.5 Mpa
- Pot life :-50-60 minutes
- Capillary absorption coefficient ($W_c 2$)= $\leq 0,20 \text{ kg}/(\text{m}^2 \cdot \text{min} 0,5)$
- W/P :-12-14%

Standard : EN 998-1;2017-02

COVERAGE

A 20Kg bag of ACC LeakBlock Waterproof Plaster - LB 101 gives ~ 10 - 12 sq. ft coverage of 10-12 mm thickness

PACKAGING, SHELF LIFE & STORAGE

- Available in 20 Kg BOPP Bag with Liner
- 6 months from the date of manufacturing
- Store in a dry place away from moisture